

# Branch-off Saddle Female Thread Outlet

February, 2021

## MATERIAL

### Body:

- Stainless Steel DIN 1.4401 (AISI 304)

### Gasket:

- EPDM

### Lugs:

- Polycarbonate.

### Compression Beam:

- Casting Type 304 (ASTM-A351-CF8)

### Bolts & Nuts

- Type 304 stainless steel.
- Rolled thread and anti galling coating.

## SPECIFICATIONS

### Temperature rating:

- -30°C/-22°F to 85°C/185°F

### Pressure rating:

- Up to 12 bar



## Stainless Steel Branch-off Saddles Female Thread Outlet

Catalog Number Coupler	OD (D) & Flange Size	H (mm)	L (mm)	Weight (kg)
47011020	110x2"	120	225	5.5
47011030	110x3"	120	225	6.3
47016020	160x2"	120	300	7
47016030	160x3"	120	300	9
47018020	180x2"	120	300	7
47018030	180x3"	120	300	9
47020020	200x2"	120	375	14
47020030	200x3"	120	375	15
47022520	225x2"	120	375	15
47022530	225x3"	120	375	15.6
47025020	250x2"	120	450	16
47025030	250x3"	120	450	17
47028020	280x2"	120	450	17
47028030	280x3"	120	450	18
47031520	315x2"	120	450	18
47031530	315x3"	120	450	20
47035520	355x2"	120	450	19
47035530	355x3"	120	450	21
47040030	400x3"	120	525	23
47045030	450x3"	120	525	24
47050030	500x3"	120	525	26
47063030	630x3"	120	525	29